








# Eslingas de Cables de Acero

## Cargas máximas de seguridad para cables de acero 6X19

Diámetro del cable		Carga de Seguridad	Carga máxima admisible en correspondencia con el ángulo para cables						
			 0°	 10°	 30°	 60°	 90°	 120°	 150°
Pulgadas	mm	Kgr.	Kgr.	Kgr.	Kgr.	Kgr.	Kgr.	Kgr.	Kgr.
5/16"	7.94	635	476	1,270	1,227	1,100	898	635	329
3/8"	9.53	897	673	1,794	1,733	1,554	1,268	897	465
7/16"	11.11	1,221	916	2,442	2,359	2,115	1,727	1,221	632
1/2"	12.70	1,600	1,200	3,200	3,091	2,771	2,263	1,600	829
9/16"	14.30	2,033	1,525	4,066	3,926	3,521	2,875	2,033	1,053
5/8"	15.90	2,540	1,905	5,080	4,907	4,399	3,592	2,540	1,316
3/4"	19.05	3,581	2,686	7,162	6,918	6,202	5,064	3,581	1,855
7/8"	22.23	4,892	3,669	9,784	9,451	8,473	6,918	4,892	2,534
1"	25.40	6,408	4,806	12,816	12,380	11,099	9,062	6,408	3,319
1 1/8"	28.60	8,117	6,088	16,234	15,682	14,059	11,478	8,117	4,205
1 1/4"	31.75	9,980	7,485	19,960	19,281	17,285	14,113	9,980	5,170
1 3/8"	34.90	12,160	9,120	24,320	23,493	21,061	17,195	12,160	6,299
1 1/2"	38.10	14,400	10,800	28,800	27,821	24,941	20,363	14,400	7,459